

DERWENT-ACC-NO: 1978-78817A

DERWENT-WEEK: 197844

COPYRIGHT 2006 DERWENT INFORMATION LTD

TITLE: Flame retardant, foamed polystyrene resin  
moulding  
forming agent prodn. - by coating the granules with crack-  
before foam moulding

PATENT-ASSIGNEE: YUKA BADISCHE KK[YUKAN]

PRIORITY-DATA: 1977JP-0023323 (March 5, 1977)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
PAGES MAIN-IPC		
<u>JP 53109565 A</u>	September 25, 1978	N/A
000 N/A		
JP 85028857 B	July 6, 1985	N/A
000 N/A		

INT-CL (IPC): C08J009/22

ABSTRACTED-PUB-NO: JP 53109565A

BASIC-ABSTRACT:

The moulding is prepd. by coating 0.01-1 w/w% of crack-forming agent, such as paraffin oil, polyethylene wax, etc. onto the surface of foaming granules of polystyrene resin contg. flame retarder, and foam-moulding the granules with steam, etc.

The granules are cracked and the swelling agent can be vapourised and scattered easily and rapidly. The crack forming agent is coated prior to pre-foaming.

TITLE-TERMS: FLAME RETARD FOAM POLYSTYRENE RESIN MOULD PRODUCE  
COATING GRANULE  
CRACK FORMING AGENT FOAM MOULD

DERWENT-CLASS: A13 A32